

ATS-8900

In-Line or Stand Alone Multiple Tabber/Stamp Affixer



- Side tabbing rather than front tabbing
- Friendly software for easy setup and smooth operation
- Fast, with speeds up to 20,000 pieces/hour placing accurate and tight closed tabs
- Solid construction, built-to-last
- Capable of handling medium range production consistently, reliably and fast
- Built-in feeder for standalone applications
- The only one available in the marketplace that tabs 1-3 tabs or stamps in-line in its price range

SPECIFICATIONS

ONE PASS TAB:	1 to 3
STANDARD TAB:	Minimum: 3/4" Maximum: 1-1/2"
STAMPS:	1 to 3
MEDIA SIZE (L X W):	Minimum: 3" x 5" Maximum: 13" x 17" (Detachable Feeder (12" X 17"))
MAX MEDIA THICKNESS:	3/8"
TAB SIZE CALIBRATION:	Fully automatic
TAB PLACEMENT SETTING:	Manual or automatic
TABE SENSOR CALIBRATION:	Manual or automatic
MEDIA HEIGHT ADJUSTMENT:	Head
TAKE-UP SPOOL:	Standard
PRODUCTION RATE:	1 TAB – 20,000 pieces/hour 2 TAB – 12,000 pieces/hour 3 TAB – 8,000 pieces/hour (11" min. piece length)
PRODUCTION RATES CALCULATD WITH:	Tri-fold 8-1/2" X 11"
REEL CAPACITY:	16" diameter 20,000 1" diameter tabs
DIMENSIONS:	25" W x 27" H (with reel) x 41" L (with feeder)

Our policy of product improvement may result in minor specification changes without notice.

Designed and Manufactured in U.S.A. by:



ASTRO MACHINE CORP.
630 Lively Blvd.
Elk Grove Village, Illinois 60007
(847) 364-6363 • Fax (847) 364 9898
www.astromachine.com

Progress Through Technology

Distributed By:

ATS-8900 04-08-