

ATS-309

In-Line or Stand-Alone

Dual Head Multiple Tabber/Stamp Affixer



- Simultaneous 2-side tabbing; Simultaneous front and side tabbing
- Easy setup and smooth operation
- Fast! Speeds up to 25,000 pieces/hour placing accurate and tightly closed tabs
- Solid construction. Built to last!
- Capable of handling medium to high production consistently and reliably
- Optional synchronized detachable feeder for stand-alone applications

SPECIFICATIONS

ONE PASS TAB:	1 to 3 per side or 1-3 on 1 side and 1 front
STANDARD TAB:	Minimum: 3/4" Maximum: 1-1/2"
STAMPS:	1 to 3
MEDIA SIZE (W X L):	Minimum: 5" x 3.5" Maximum: 11" x 15" (Detachable Feeder (12" X 17")
MAX MEDIA THICKNESS:	1/4"
TAB SIZE CALIBRATION:	Manual or automatic
TAB PLACEMENT SETTING:	Manual or automatic
TAB SENSOR CALIBRATION:	Manual or automatic
MEDIA HEIGHT ADJUSTMENT:	Tabbing Heads move up and down
TAKE-UP SPOOLS:	Two included
PRODUCTION RATE:	Two sides tabbed simultaneously (1 tab - 25,000/h) Two sides tabbed simultaneously (2 tabs - 15,000/h) Two sides tabbed simultaneously (3 tabs - 10,000/h)
PRODUCTION RATES CALCULATD WITH:	Tri-fold 8-1/2" X 11"
REEL CAPACITY:	Two reels, 12" diameter each
DIMENSIONS:	28" W x 26" H (with reels) x 34" L (with feeder)
WEIGHT:	97 lbs.
ELECTRICAL:	115VAC, 50/60Hz 240VAC 50/60 Hz available

Our policy of product improvement may result in minor specification changes without notice.

Designed and Manufactured in the U.S.A. by:



ASTRO MACHINE CORP.
630 Lively Blvd.
Elk Grove Village, Illinois 60007
(847) 364-6363 • Fax (847) 364 9898
www.astromachine.com

Progress Through Technology

Distributed By: